



Installation Instructions
BILLET CLUTCH COVER
YZ/WR450F, YZ250, YZ/WR250F, YZ125, YZ85
GYT-5XD35-10-AL, GYT-5XF35-10-AL, GYT-5XC35-10-AL,
GYT-1C335-10-AL, GYT-5PA35-10-AL

Please read and understand these instructions completely before installation to avoid any possible injury to yourself or damage to your motorcycle and/or accessory.

Dealer:

These instructions contain important information for future reference and must be given to the customer.

1. Parts List:

Item	Part Name	Description	Qty
1	Clutch cover	Billet	1
2	Gasket	See Dealer	1

2. Removal & Installation:

- a) Turn the petcock to the 'OFF' position, plug the gas tank vent and lay bike on its left side. Check to make sure no fuel is leaking from the gas cap or vent before proceeding.

⚠WARNING Gasoline and its vapors are highly flammable and explosive.

- b) If required, remove the brake pedal from the bike by following all the steps in your Yamaha service manual.
c) Remove all the stock bolts that hold the stock clutch cover, and retain the hardware for installation.
d) Inspect the gasket for damage, if damage has occurred remove the gasket and replace with the gasket provided, item # 2.
e) Install the GYT-R billet clutch cover item # 1 with the stock bolts. Snug the bolts in a crisscross pattern.
Torque to 10 Nm (7.2 ft. lbs)
f) Install the brake pedal if removed previously.

- 3. Maintenance:** Periodically check all fasteners for tightness and re-torque as required

- 4. Care and Cleaning:** Wash with soap and water.

- 5. Customer Service:** For more information regarding installation please contact your YAMAHA dealer.