



INSTALLATION INSTRUCTIONS
GYTR Billet Pressure Plate
GYT-2S256-20-00

YFZ450, YZ/WR450F/YZ250, YZ/WR 250F/YZ125
GYT-5DX56-20-00, GYT-5TG56-40-00, GYT-5XC56-20-00



⚠ WARNING

Please read and understand these instructions completely before installation to avoid possible injury to yourself, or damage to the accessory or vehicle.

CAUTION:

- This installation should be performed by an authorized Yamaha dealer or a qualified mechanic. Some components require information from the model's service manual for proper installation or adjustment. Be sure to have the service manual on hand, if necessary, before proceeding with the installation.
- Alteration of emission-related components constitutes tampering under Federal and State laws and can lead to substantial fines and penalties if used other than in closed-course competition.
- Engine-related competition parts are intended for closed-course racing applications only.

DEALER:

These instructions contain important information for future reference and *must* be given to the customer.

WARRANTY INFORMATION:

- Genuine Yamaha GYTR components are covered by a 90-day warranty against defects in material or workmanship. Labor for replacement of defective components is not covered. See your Yamaha dealer for a copy of the warranty statement.
- The Limited Warranty provided with new Yamaha vehicles has exclusions for certain failures, including those caused by competition or racing use (except YZ and WR motorcycle models) as well as by abnormal strain or abuse. While installation of these GYTR components will not "void" your vehicle's warranty, specific failures adjudged by Yamaha to have resulted from the installation of accessory components or other modifications, or from competition use (except YZ and WR motorcycle models), may not be covered by warranty or Yamaha Extended Service.

1. PARTS LIST:

This kit contains the following components. Before beginning installation confirm there are no missing or damaged components.

Item #	Part Number	Description	Qty
1	*	GYTR Billet Pressure Plate	1

* Part supplied with kit only and not available separately.



2. PREPARATION:

- Place motorcycle on a secure stand.
- Clean all mounting surfaces before beginning installation.

3. INSTALLATION:

- Remove the pressure plate from motorcycle. (Refer to owner's service manual)
- Install you new GYTR Pressure Plate. (Refer to owner's service manual)

Torque GYTR Pressure Plate to:

YZ125	YZ/WR250F	YZ250	YZ/WR450F	YFZ450
10 Nm (7.2 ft·lb)	8 Nm (5.8 ft·lb)	10 Nm (7.2 ft·lb)	8 Nm (5.8 ft·lb)	8 Nm (5.8 ft·lb)

4. MAINTENANCE:

Replace transmission fluid, often, following the maintenance procedure outlined in your owner's service manual. Replacing fluids will extend the life of your pressure plate and provide the best performance..

5. CUSTOMER SERVICE:

For further information see your Yamaha dealer.

ESTIMATED TIME TO INSTALL: 0.2 HRS