



Installation Instructions Carbon Fiber Tank Trim Panels for YZF-R1 GYT-5VY49-27-00

Please read and understand these instructions completely before installation to avoid any possible injury to yourself or damage to your motorcycle and/or accessory.

Dealer:

These instructions contain important information for future reference and must be given to the customer.

1. Parts List:

ITEM	PART NAME	DESCRIPTION	QTY
1	Carbon Fiber Tank Trim Panel	left	1
2	Carbon Fiber Tank Trim Panel	right	1

2. Removal/Installation:

- a) Remove the stock seat by removing the two allen head screws located under the rear of the seat foam.
- b) Remove the stock fastener holding the left side OE plastic tank trim in place.
- c) Carefully slide the OE trim towards the rear of the bike to remove it, this piece is held on by a slip on/off system.
- d) Once the OE trim panel is removed install the CF piece, item 1, by sliding it into the two slip-fit fasteners and then install the stock screw in the rear hole.
NOTE: Use extreme care and caution when installing and removing these trim pieces.
- e) Repeat steps b) through d) for the right side, item 2.
- f) Re-install the seat.

3. Maintenance:

Periodically check and restore bolts to specification.

4. Care and Cleaning:

Wash with soap and water. Avoid contact with harsh cleaners and solvents.

5. Customer Service:

For more information regarding installation please contact your YAMAHA dealer.