

Installation Instructions

Frame Slider Kit-04 YZF-R1

GYT-5VY33-00-BK

Please read and understand these instructions completely before installation to avoid any possible injury to yourself or damage to your motorcycle and/or accessory.

Dealer:

These instructions contain important information for future reference and must be given to the customer.

1. Parts List:

ITEM	PART NAME	DESCRIPTION	QTY
1	Hex Bolt	M10 x 1.25P x 110mm	2
2	Flat Washer	12.95 ID x 23.80 OD x 2.58 THK	2
3	Slider Protector	Delren	2
4	Flat Washer	21.25 ID x 36.56 OD x 2.67 THK	2
5	Spacer	Billet Aluminum	2

Installation:

Place motorcycle securely on its side stand.

2. Removal:

- a) Remove the 10mm bolt shown in photo shown below.



3. Installation:

- b) Place item 2, flat washer onto item 1, Hex bolt. Slide the slider, item 3 onto the bolt followed by the large flat washer, item 4 and then the billet spacer, item 5.
- c) Place the frame slider assembly onto the vacated hole and tighten.
Torque to 40Nm-4.0mkg-28.8ftlbs.

4. Maintenance:

Periodically check and restore bolts to specification.

5. Customer Service:

For more information regarding installation please contact your YAMAHA dealer.